



## Tools Needed

### STEP 1.

Vehicle surface must be clean, dry and free of dirt and debris, especially in the wheel well area, behind the lower part of the headlight openings and the underside of the nose (just above the license plate). Make sure the front of the car has a good coat of wax, or two, before installing mask. Place mask in direct sunlight to allow the material to stretch easier during installation. Ideal temperature is about 80 degrees for proper stretch.

NOTE: *For the 1980-82 Mini Front End Mask skip steps #2 and #3.*

### STEP 2.

Adhere 2-3" adhesive backed velcro pieces directly above the front license plate on the under side of nose, Illustration (A).

### STEP 3.

Attach to the 2 corresponding pieces of velcro sewn into the center point of the mask. These may need to be readjusted later, Illustration (B).

### STEP 4.

Lay the driver's side of the mask onto the surface of the car and pull around to the fender opening. Roughly align the hole opening in the mask with the side marker light and bend the 2 extended tabs around the fender, Illustration (C).

### STEP 5.

Repeat step # 2 on the passenger side of the car.

### STEP 6.

Mask will need to be re-tightened on the sides. Work back and forth tightening the bendable tabs until the mask is tight, and the marker lights line up correctly. Then stretch the elastic hook over to the hole just under the license plate, Illustration (D).



Continued >

## – Mini Front End Mask

### STEP 7.

Reach under and manually lift the driver side headlight assembly (about TWO THIRDS of the way open, just so they don't lock open), Illustration (E). It is helpful to have someone hold the assembly in this position, while you adhere the 12" adhesive backed velcro piece under the bottom of the headlight opening, Illustration (F). Once the velcro is in place, match the top edge of the binding sewn onto the top of the mask with the top of the headlight opening. (Make sure it will not restrict the headlight lid from closing.) Wrap the soft velcro extension over the bottom of the headlight opening, so it grabs the 12" adhesive velcro strip, Illustration (G). Repeat procedure on the passenger side.

### STEP 8.

If you unhooked the 2 velcro pieces above the license plate, you will need to pull the mask downward and reattach to the corresponding velcro, Illustration (H).

### STEP 9.

On each side of the mask, where the two bendable tabs wrap around the fender wheel well, you will notice a bulge in the mask between the tabs. Push the top tab upward and the bottom tab down, in order to position the two adhesive backed velcro pieces inside the fender wheel well, Illustration (I). These two velcro pieces will help hold the top tab up, and the bottom tab down, thus removing the bulge.

### STEP 10.

At this point the mask is in place. You may need to go around and tighten and adjust for the best fit.

### STEP 11.

After driving or exposure to the sun, the mask material will stretch and may need to be tightened.

